

1.8 GHz, 1.9 GHz AND 2.4 GHz
CORDLESS PHONE
THAT SUPPORTS MULTIPLE REDIDOCK™
HANDSETS WITHIN THE ROOM.

OPAL DECT SERIES

Cordless Telephone



Opal RediDock

Opal DCT Cordless

Cetis 

Scitec • Teledex • TeleMatrix

CetisGroup.com

OPAL DECT SERIES

Cordless Telephone

Features

- Single or Two line DECT configuration
- Certified for DECT 1.8 GHz, DECT 1.9 GHz, and DCT 2.4 GHz. for best range, clarity & security
- Single or Two line configuration
- Superior Quality Speakerphone for convenient Hands-free calls
- Two lines with conference*
- PrimeLine/RingLine Select™ automatically chooses the correct available line
- AutoSync – handset automatically syncs with base unit when in cradle
- ExpressNet™ broadband-ready
- Easy-access data port
- Up to ten programmable guest service buttons
- Last number redial
- Lighted handset keypad
- Handset page/locator
- Low battery indicator
- Breakage-resistant, non-extending antenna
- Large printable faceplate area
- Line status indicators*
- Bright message wait lamp and positive charge indicator
- morePhone™ Overage Program with each qualifying shipment of Cetus telephones includes extra sets at no charge.
- Standard warranty applies (teledex.com)



Models

- Single line Speakerphone: 5 or 10 guest service keys
- Two line Speakerphone: 5 or 10 guest service keys
- RediDock Single line
- RediDock Two line

Colours

Ash and Black

**Two-line models only*

Specifications:

Standard Colour:	Ash and Black
Footprint:	6.0" x 9.0" (15.24cm x 22.86cm)
Footprint (RediDock):	2.75" x 8.17" (7.0cm x 20.08cm)
Weight:	2.0 lbs. (0.9kg)
Weight (Redidock):	7 oz. (0.2kg) (without handset) 12 oz. (0.34kg) (with handset)
Frequency:	2.4 GHz, 1.9 GHz or 1.8 GHz
Power:	9 VDC adapter
Standby time:	14 days
Talk time:	4 hours
Humidity:	65% ± 20%
Temperature:	77°F ± 50° (25°C ± 10°C)

Packaging:	12 per carton
Packaging (RediDock):	20 per carton
Faceplate Size:	Full length
FCC Specifications:	Meets or exceeds Part 15, Subpart J, Class A, Part 68
Safety Standard:	ETL and CE
Operating Voltage:	24 to 56 VDC Non-Polarity
Flash Timing:	.600 ms
Ringer Equivalence:	Z (Use only behind PBX)
Handset:	Hearing Aid compatible
Line Cord:	15-foot, 2 RJ45

Part Numbers:

DECT 1.9 GHz (Single line)	DECT 1.9 GHz (Two line)	DECT 1.8 GHz (Single line)	DECT 1.8 GHz (Single line)
Opal DCT1905	Opal DCT2905	Opal DCT1805	Opal DCT2805
OPL95149 Ash	OPL97149 Ash	OPL95148 Ash	OPL97148 Ash
OPL951491 Black	OPL971491 Black	OPL951481 Black	OPL971481 Black
Opal DCT1910	Opal DCT2910	Opal DCT1810	Opal DCT2810
OPL95339 Ash	OPL97359 Ash	OPL95338 Ash	OPL97358 Ash
OPL953391 Black	OPL973591 Black	OPL953381 Black	OPL973581 Black
RediDock	RediDock	RediDock	RediDock
RD1910 (Single-line)	RD2910 (Two-line)	RD1910 (Single-line)	RD2810 (Single-line)
OPL95339HDKIT Ash	OPL97359HDKIT Ash	OPL95338HDKIT Ash	OPL97358HDKIT Ash
OPL953391HDKIT Black	OPL973591HDKIT Black	OPL953381HDKIT Black	OPL973581HDKIT Black

Cetus, Inc. Worldwide Headquarters

5025 Galley Road, Colorado Springs, CO 80915

North America Toll Free 1 800 462 9446 • Telephone +1 719 638 8821 • Fax +1 719 638 8815 • info@cetusgroup.com • cetisgroup.com



Scitec • Teledex • TeleMatrix