





Features 9600IP SERIES SIP DECT Cordless

► SIP 2.0 compatible and IAX2 - ready

TELEMATRIX.

- Avaya certified, Mitel certified, Alcatel-Lucent certified, Siemens certified, Asterisk compatible, and more.
- ▶ Most secure and clear cordless transmission & reception available
- ▶ Supports up to 3 remote handset kits per base
- ► Professional quality speakerphone
- ► Convenient feature keys speaker, redial, handset locate, mute, hold
- ► Three way conference calling (2 line models only)
- ► TouchLite® one-touch voice mail retrieval lightbar technology
- ► 5 or 10 guest service keys
- ▶ Dual-Port 10/100Mb switched Ethernet port on base for HSIA

Colors

- ▶ Black or Ash
- ▶ 7 Standard colored inserts also available. (minumim quantities apply)*

7 Standard Colored Inserts



Questions: info@telematrix.net Service: customerservice@telematrix.net

Web Site: www.telematrix.net

9600IP Series • Remote Charging Stations IP DECT SIP Cordless Features & Specifications:

9600IP Series **IP DECT SIP Cordless Speakerphones**

Product Identification & Order Numbers:

Single Line:	Two Line: (2-L models	s available 02 '00
•	THO EITO: (2 E MOGOIC	savanabio Q2 ot
► 5 guest service keys		
9600IP-MWD5	9602IP-MWD	Colour
DECT 6.0 Domestic:		
P/N 964591 IP	P/N 984591 IP	black
P/N 96459 IP	P/N 98359 IP	light ash
DECT 1.8GHz International:		
P/N 962591 IP	P/N 982591 IP	black
P/N 96259 IP	P/N 98259 IP	light ash
► 10 quest service keys		
9600IP-MWD	9602IP-MWD	
DECT 6.0 Domestic:		
P/N 965591 IP	P/N 985591 IP	black
P/N 96559 IP	P/N 98559 IP	light ash
DECT 1.8GHz International:		
P/N 963591 IP	P/N 983591 IP	black

▶ Remote handset charging stations.... up to 3 per base.

9600IP-HDKIT	9602IP	-HDKIT

DECT 6.0 Domestic:

P/N 96359**IP**HDKIT

P/N 96359IP

P/N 965591 IP HDKIT	P/N 985591 IP HDKIT	black
P/N 96559 IP HDKIT	P/N 985591 IP HDKIT	light ash
DECT 1.8GHz International:		
P/N 963591 IP HDKIT	P/N 983591 IP HDKIT	black

P/N 983591**IP**HDKIT

P/N 98359IP

light ash

► For Coloured Insert part numbers, add the following suffixes at the end of the ash or black P/N number. *

> Orange = ORG / Blue = BLU / Lime = LIM / White = WHI Gray = GRA / Ochre = OCH / Red = RED

- * Example: 9600IP-MWD5 6.0 black with orange insert = 964591**IP**-ORG
- * Example: 9602IP-MWD 1.8 ash with red insert = 983591IP-RED
- ► Custom Colours available in minimum quantities *
 - ▶ 100 249 units with '7 Standard' coloured inserts are available at an Additional Charge
 - ▶ 250 or more of '7 Standard' colour inserts are No Charge
 - ▶ 500 or more of Custom coloured telephones are No Charge

Audio/Visual Features:

- ► Exceptional Quality Speakerphone
- ▶ Bright red, TouchLite® one-touch voice mail retrieval lightbar
- ► One-Touch message retrieval also located handset, press & hold 1 key
- ► Multi Step Speaker and Handset Volume Control
- ► Three Way Conference Calling (2 line models only)
- ► High/Low Ringer Volume Switch
- ► LED Indication for Speaker & Mute Keys (all models)
- ► LED Indication for Hold. Line 1 & Line 2 Keys (2 line models only)
- ► Handset Locator Button with Audio Indication
- ▶ Battery Charging Indicator Light on Base & Multi Station

Deluxe Features:

- ▶ Deluxe VoIP DECT Cordless Speakerphone
- ► SIP Compatible and IAX2 ready
- ▶ DECT 6.0 SIP for N. America and DECT 1.8GHz SIP for International
- ▶ Most Secure and Clear Cordless Transmission and Reception Possible
- ▶ Up to Ten Configurable Soft Keys (line & features)
- ▶ Dual-Port 10/100Mb switched Ethernet port on base for HSIA
- ► On-Hook Pre-Dialing on guest service Keys
- ► Supports up to 3 additional Multi Handset Stations
- ► Independent Simultaneous Handset and Base Operation
- ► Handsets are Reprogrammable to All Bases
- ► Handset may face front or back (Dual Facing) while charging in Multi Charging Stations
- ► Full Length Custom Tailored Faceplates on Base
- ► Industrial Grade Construction with Matte Finish Design
- ► Non-Slip Base

Network Features:

- ▶ Dual-Port Two 10/100Mb Switched Ethernet Port for HSIA
- ► Supports IEEE 802.1 p/q for Quality of Service / VLAN Priority Tagging
- ▶ 3.5W = Class 2 Accepts Standard Based (IEEE 802.3 af) Power over Ethernet
- Compression Support G.711, G.723.1, G.726, G.729A/B

Product Information:

- ► Installation Includes
 - ▶ Base unit includes Cordless Handset with Battery & RJ45 line cord
 - ▶ Remote Charging Station includes Handset with Battery & A/C adaptor
- ► Handset: Talk Time = 6 hours, Standby Time = 10 days, Range = 100ft./30m
- 9.5"/23.75cm(I) 6.75"/16.87cm(w) 3.5"/8.75cm(h) ▶ Unit Dimensions: ► Packaging: Weight MasterPack Quantities of 10 Units, 36.6lbs/16.6kg
- Certifications

FCC Part 68, FCC Part 15 & UL 1459 Ref. CE & ETL, ADA/FCC Hearing Aid Compliant

Switch Certifications:

- ▶ Mitel Certified single line models
- ► Alcatel-Lucent Cerified single line models
- ▶ Digium Premier Interoperable Partner 'The Asterisk Company'
- ▶ NEC Univerge Certified single & two-line corded 3300IP models









